

# PALLET STRAPPING MACHINES

# STP

## 2800 9700

### Saves your time and cost of packaging material

- Easy to operate
- Easy to maintain
- Economical in daily use
- Easy to move around with 4 wheels fitted
- Solid design
- Easy to adjust strapping tension
- Optional frame sizes

### General technical Specifications

<b>Sealing material:</b>	PP, PET Strapping belt, width 12 mm. Thickness 0.5 – 0.8 mm. Belt strapping strength > 1500 N
<b>Strapping tension:</b>	1000 – 1500 N
<b>Packing capacity:</b>	5 sec./ cycle, depending on operator

### STP 2800

- Automatic belt channel feed
- Automatic product strapping

<b>Max. product size (WxH):</b>	850 x 2600 mm.
<b>Min. product size (WxH):</b>	350 x 1100 mm.
<b>Machine dimensions (LxWxH):</b>	3100 x 980 x 2900 mm.
<b>Power:</b>	230 Volt, 50 Hz, 2.2 kW
<b>Weight:</b>	820 kg.



### STP 9700

- Semi-Automatic product strapping

<b>Max. product size (WxH):</b>	Unlimited
<b>Min. product size (WxH):</b>	900 mm.
<b>Machine dimensions (LxWxH):</b>	920 x 644 x 1320 mm.
<b>Power:</b>	230 Volt, 50 Hz, 1 kW
<b>Weight:</b>	305 kg.

